

AQ-4000

Features

The Aqua Phase Model AQ-4000 is the largest unit presently produced in the Aqua Phase line. This unit is designed to handle requirements placed on hospitals, (many times implemented themselves) to improve their infection control programs and protocols.

The AQ-4000 is a stationary unit with options allowing the item being washed to be placed in from one end and removed from the same, or a pass-through model which allows items to be loaded in one end of the machine and removed from the other.

The AQ-4000 has a movable conveyor floor in the wash chamber as an optional feature. Items can be placed just inside the door and, at the turn of a switch, moved forward into the wash chamber to allow more room for additional items to be washed. When the AQ-4000 is ordered with the Disinfection Application System, it will become an integral part of your infection-control protocols.

Like all Aqua Phase models, in order to operate the machine once the unit is located, all you need to do is hook up two hoses, one for the hot water fill and one for the drain, plug the Aqua Phase in and begin saving time, improving efficiency and enhancing infection-control.

Standard Features - AQ-4000:

- Stainless Steel Construction and Spray Arms
- Double Walled
- Front Door Safety Glass Window
- Variable Wash Time Cycles (3, 5, or 7 minute)
- Rinse Cycle System
- 240 Volt 50/60 Hz Operation
- Hot Water Hose Set (Set of 2 – 3m)

Options – AQ-4000:

- Double door Pass-Through Upgrade
- Disinfectant Application System
- Conveyor Transfer System
- Heavy Duty Caster Wheels
- Utility Wash Trays
- Electronic Temperature Monitor
- Lighted Wash Chamber
- Air Dry Blower
- Utility Chamber Floor
- Special Time Cycles
- Long Hot Water Hose Set (Set of 2 – 7.5m)

Design Features - AQ-4000:

Construction (Stainless Steel)	Double Walled
System Controls Are By	Logic Controller
Spray Arm Assemblies	Stainless Steel
Tested to European Specs.	Yes
UL Listed Electronics Assembly	Standard
Rinse Cycle	Standard
Cleaner Injection System	Peristaltic
Wash Cycle Lengths	3,5 or 7 minutes
Disinfectant Application (Optional)	Automatic
Filter Clogging Signal	Standard
Water Level Sensor	Electronic
GFCI Breaker in Power Cord	Standard
Safety Switch Front & Rear	Standard
Maximum AMP Draw	12.75
Warranty - Wash Chamber	5 Years
Warranty – Parts	1 Year
Warranty – Labor	90 Days

Dimensions - AQ-4000:

Machine Outside Width	1607 mm
Machine Outside Length	2458 mm
Machine Outside Height	1855 mm
Wash Chamber Width	1029 mm
Wash Chamber Height	1232 mm
Wash Chamber Length	2382 mm



Aqua Phase

PO BOX 3514, RUNDLE MALL SA 5000

PHONE: +61 8 7200 4226 FAX: +61 8 8121 7668 MOBILE: +61 419 296 694
EMAIL: sales@aquaphase.com.au WEB: www.aquaphase.com.au