

## AQ-1500

### Features

Aqua Phase Model AQ-1500 is designed specifically for smaller size nursing homes, home medical equipment and durable medical equipment dealers. Like all models, the AQ-1500 will save your staff a tremendous amount of time, improve your infection control program and make one of the most disliked tasks in your facility far more enjoyable.

AQ-1500 is the first in the Aqua Phase series to offer oscillating spray arms. The key components such as the valves, pumps and nozzles are identical to the ones used in the more expensive models produced. AQ-1500 includes a stainless steel water/spray distribution system with a double-wall stainless steel chamber and an individual wash cycle time length of 3,5 or 7 minutes.

Like all Aqua Phase models, in order to operate the machine once the unit is located, all you need to do is hook up two hoses, one for the hot water fill and one for the drain, plug the Aqua Phase in and begin saving time, improving efficiency and enhancing infection control.

### Standard Features - AQ-1500:

- Stainless Steel Construction and Oscillating Spray Arms Single-Wall
- Double-Wall Stainless Steel Chamber
- Electronic Controls - Variable Wash Times (3,5 or 7 minute)
- Rinse Cycle System
- Heavy Duty Casters
- Seal welded wash chamber
- Automatic filling and draining
- 1 HP Motor / Stainless Steel pump



### Options – AQ-1500:

- Disinfectant Application Systems
- Front Door Safety Glass Window
- Wheelchair Wheel Rotation (Front & Rear)
- Equipment Loading Wash Rack
- Utility Wash Trays
- Electronic Temperature Monitor
- Loading Ramps
- Multi-Size Wheel Rotator
- Long Hot Water Hose Set (Set of 2 – 7.5m)

### Design Features - AQ-1500:

- |                                  |                   |
|----------------------------------|-------------------|
| • Construction (Stainless Steel) | Double Wall       |
| • System Controls Are By         | Logic Controller  |
| • Spray Arm Assemblies           | Stainless Steel   |
| • UL Listed Electronics Assembly | Standard          |
| • Rinse Cycle                    | Standard          |
| • Cleaner Injection System       | Peristaltic       |
| • Wash Cycle Lengths             | 3, 5 or 7 minutes |
| • Filter Clogging Signal         | Standard          |
| • Water Level Sensor             | Electronic        |
| • GFCI Breaker in Power Cord     | Standard          |
| • Safety Switch Front & Rear     | Standard          |
| • Maximum AMP Draw               | 16.5              |
| • Warranty - Wash Chamber        | 5 Years           |
| • Warranty – Parts               | 1 Year            |
| • Country of Manufacture         | USA               |



### Dimensions - AQ-1000:

Machine Outside Width	864 mm
Machine Outside Length	1729 mm
Machine Outside Height	1607 mm
Wash Chamber Width	654 mm
Wash Chamber Height	965 mm
Wash Chamber Length	1264mm