

## Medical Equipment Washing and Decontamination Systems

# **AQ-3000**

#### **Features**

**Aqua Phase Model AQ-3000** is the work horse of the Aqua Phase line. AQ-3000 is designed and built to handle the heavy washing requirements of large long term care facilities, large home medical and durable medical equipment dealers, and hospitals.

The AQ-3000 with the Disinfection Application System will be an integral part of your infection control protocols. Some units of Model AQ-3000 have had tens of thousands of cycles ran through them and are still going strong. AQ-3000 features double wall Stainless Steel construction to act as a heat insulator. The AQ-3000 is mounted on four large, durable casters to allow for easy relocation and The AQ-3000 comes standard with the Disinfection Application System, the Wheel Rotation System for wheelchair wheels and Safety Glass Window.

One of the key additional standard features of the AQ-3000 is the wall mounted studs. This allows you, now or in the future, to order the Utility Wash Trays System. More importantly, it allows you to customize your own racking system to handle your specific wash needs.

### Standard Features - AQ-3000:

- Stainless Steel Construction and Spray Arms
- Double Walled
- Disinfectant Application System
- Front Door Safety Glass Window
- Variable Wash Time Cycles (3, 5, or 7 minute)
- Rinse Cycle System
- Rotation of Wheelchair Wheels (Front & Rear)
- Heavy Duty Casters
- Hot Water Hose Set (Set of 2 3m)

## Options - AQ-3000:

- Equipment Loading Wash Rack
- Utility Wash Trays
- Electronic Temperature Monitor
- Lighted Wash Chamber
- Air Dry Blower
- Utility Chamber Floor
- Multi-Size Wheel Rotator
- Special Time Cycles
- 220 Volt 50/60 Hz Operation
- Long Hot Water Hose Set (Set of 2 7.5m)

## Design Features - AQ-3000:

Construction (Stainless Steel) Double Walled Logic Controller System Controls Are By Spray Arm Assemblies Stainless Steel Tested to European Specs. Yes Standard **UL Listed Electronics Assembly** Rinse Cycle Standard Cleaner Injection System Peristaltic Wash Cycle Lengths 3,5 or 7 minutes Disinfectant Application (Optional) Automatic Standard Filter Clogging Signal Water Level Sensor Electronic GFCI Breaker in Power Cord Standard Safety Switch Front & Rear Standard Maximum AMP Draw 12.6 Warranty - Wash Chamber 5 Years Warranty - Parts 1 Year

## Dimensions - AQ-3000:

Machine Outside Width860 mmMachine Outside Length1676 mmMachine Outside Height1600 mmWash Chamber Width673 mmWash Chamber Height1300 mmWash Chamber Length990 mmShipping Weight545 kg





